

MODEL YEAR 2025 | FAT BOY GRAY GHOST

Dimensions	FLSTFI Fat Boy® Gray Ghost	Notes
Length	93.1 in. (2,365 mm)	
Overall Width	40 in. (965 mm)	
Overall Height	44.1 in. (1,120 mm)	
Seat Height, Laden	25.9 in. (658 mm)	2
Seat Height, Laden (Low seat position)		
Seat Height, Laden (High seat position)		
Seat Height, Laden (Low seat position with optional ARH suspension)		
Seat Height, Laden (High seat position with optional ARH suspension)		
Seat Height, Unladen	26.6 in. (675 mm)	
Seat Height, Unladen (Low seat position)		
Seat Height, Unladen (High seat position)		
Seat Height, Unladen (Low seat position with optional ARH suspension)		
Seat Height, Unladen (High seat position with optional ARH suspension)		
Static Ground Clearance	4.9 in. (125 mm)	
Dynamic Ground Clearance (with optional suspension)		
Rake (steering head)	30	
Fork Angle	32	
Trail	4.1 in. (104 mm)	
Wheelbase	65 in. (1,650 mm)	
Tires, Type	Michelin® Scorcher 11, front and rear	
Tires, Front Model	Scorcher 11	
Tires, Front Specification	160/60R18,70V,BW	
Tires, Rear Model	Scorcher 11	
Tires, Rear Specification	240/40R18,79V,BW	
Fuel Capacity	5 gal. (18.9 l)	

Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5 qt. (4.7 l)	
Transmission Capacity	1 qt. (.95 l)	
Primary Chain Case Capacity	1.43 qt. (1.35 l)	
Coolant Capacity	N/A	
Weight, As Shipped	668 lb. (303 kg)	
Weight, In Running Order	694 lb. (315 kg)	
Gross Vehicle Weight Rating	1,175 lb. (533 kg)	
Gross Axle Weight Rating, Front	450 lb. (204 kg)	
Gross Axle Weight Rating, Rear	760 lb. (345 kg)	
Luggage Capacity -Volume	N/A	

Engine	FLSTFI Fat Boy® Gray Ghost	Notes
Engine	Milwaukee-Eight® 117 Custom	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore	4.075 in. (103.5 mm)	
Stroke	4.5 in. (114.3 mm)	
Displacement	117 cu in (1,923 cc)	
Compression Ratio	10.3:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	9 in. (229 mm) round, center bolt cover with washable fiberglass filter media	
Exhaust	2-into-2 staggered; catalyst in muffler	
Lubrication System	Pressurized, dry-sump with oil cooler	

Drivetrain	FLSTFI Fat Boy® Gray Ghost	Notes
Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 32/66 ratio	
Clutch	Mechanical, 10 plate wet, assist & conventional	
Transmission	6-Speed Cruise Drive®	
Gear Ratios (overall) 1st	9.311	

Gear Ratios (overall) 2nd	6.454	
Gear Ratios (overall) 3rd	4.793	
Gear Ratios (overall) 4th	3.882	
Gear Ratios (overall) 5th	3.307	
Gear Ratios (overall) 6th	2.79	

Chassis	FLSTFI Fat Boy® Gray Ghost	Notes
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; MIG welded; aluminum forged fender supports	
Swingarm	Mild steel, tubular sections, stamped x-member, forged axle junctions; MIG welded; removable belt spacer	
Front Fork	Dual-bending valve 49 mm telescopic with aluminum fork triple clamps; dual rate spring; "beer can" covers	
Front Fork, Optional		
Rear Shocks	Hidden, free piston, coil-over monoshock; 43mm stroke; hydraulic preload adjustment	
Rear Shocks, Optional		
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Machined, Lakester cast aluminum	4
Wheels, Front Diameter	18 in. (457 mm)	
Wheels, Front Width	4.5 in. (114 mm)	
Wheels, Rear Type	Machined, Lakester cast aluminum	4
Wheels, Rear Diameter	18 in. (457 mm)	
Wheels, Rear Width	8 in. (203 mm)	
Brakes, Caliper Type	4-piston fixed front and 2-piston floating rear	
Brakes, Rotor Type	Front and rear silver, Split 7-spoke floating rotors	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5 mm)	
Brakes, Front is dual	No	
Brakes, Rear Diameter	11.5 in. (292 mm)	
Brakes, Rear Thickness	0.23 in. (5.8 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	5.1 in. (130 mm)	
Suspension Travel, Rear	3.4 in. (86 mm)	

Performance	FLSTFI Fat Boy® Gray Ghost	Notes
Engine Torque Testing Method	J1349	
Engine Torque	122 ft-lb (166 Nm)	5
Engine Torque (rpm)	3000	
Power	101 HP / 75 kW @ 4800 rpm	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	25.6	
Lean Angle, Left (deg.)	25.6	

Electric	FLSTFI Fat Boy® Gray Ghost	Notes
Battery	Sealed, maintenance-free, absorbed glass mat (AGM) battery, 12V, 17.5Ah, 310 CCA at 0°F	
Charging	Three-phase, 48 Amp system (364 Watts @13 Volts, 900 rpm, 624 Watts max power @ 13 Volts, 2000 rpm)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	All LED headlamp, low and high beam with signature position lighting	
Lights (as per country regulation), Tail/Stop	Bullet-style, LED stop/tail/turn signals	
Lights (as per country regulation), Front Signal Lights	LED Bullet Turn Signals	
Lights, Rear Turn Signals	LED Bullet Turn Signals	
Gauges	5-inch analog speedometer with digital gear, odometer, fuel level, ride modes, heated gear, traction control, ABS, TPMS, cruise control, clock, trip, range and tachometer indication	
Auxiliary Lamps	N/A	
Electric Power Outlet	USB C-Type , Output 5V at 2.4 Amp	
GPS System	N/A	
Reverse Gear	N/A	

Fuel Economy & CO₂ Emissions	FLSTFI Fat Boy® Gray Ghost	Notes
Fuel Economy Testing Method	Estimated City/Hwy	

Fuel Economy	49 mpg (4.8 l/100 km)	
--------------	-----------------------	--

Infotainment	FLSTFI Fat Boy® Gray Ghost	Notes
Infotainment system	N/A	
Screen Size	N/A	
Type	N/A	
Watts Per Channel	N/A	
Speakers	N/A	
Speaker Size	N/A	
Headset Specifications (if equipped)	N/A	
AM	N/A	
FM	N/A	
MW	N/A	
LW	N/A	
Weather Band (WB)	N/A	
SD Card, Flash Drive and MP3 - via USB Connection	N/A	
Hands-free Mobile Phone - via Bluetooth	N/A	
Voice Recognition Languages: Phone functions only	N/A	
Rider/Passenger Intercom	N/A	
Vehicle Information Screen (Air temperature, oil pressure and EITMS)	N/A	
Text-to-Speech (TTS) Languages	N/A	
USB	N/A	
Phone Connectivity	N/A	
Bluetooth	N/A	
Navigation - via Bluetooth	N/A	

Rider Safety Enhancements	FLSTFI Fat Boy® Gray Ghost	Notes
Anti-lock Brake System (ABS)	Included	
Electronic Linked Braking (ELB)	N/A	
Traction Control System (TCS)	Included	
Drag-torque Slip Control System (DSCS)	Included	

Vehicle Hold Control (VHC)	N/A	
Tire Pressure Monitoring System (TPMS)	Included	
Wheel Lift Mitigation	N/A	

Cornering Rider Safety Enhancements	FLSTFI Fat Boy® Gray Ghost	Notes
Cornering Enhanced Anti-lock Brake System (C-ABS)	Included	
Cornering Enhanced Electronic Linked Braking (C-ELB)	N/A	
Cornering Enhanced Traction Control System (C-TCS)	Included	
Cornering Drag-Torque Slip Control System (C-DSCS)	Included	
Enhanced Lift Mitigation	N/A	

Warranty And Service	FLSTFI Fat Boy® Gray Ghost	Notes
Warranty		
Service Interval		

FootnotesFLSTFI Fat Boy® Gray Ghost		
1	<p>Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest</p>	

	information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.	
2	Measurement reflects 180 lb. (81.7 kg) operator weight.	
3	Recommended 91 octane or higher fuel (R+M)/2.	
4	Standard and optional wheels may vary by country and region.	
5	Values shown are nominal. Performance may vary by country and region.	

©2025 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.