

MODEL YEAR 2025 | TRI GLIDE[®] ULTRA

Dimensions	FLHTCUTG Tri Glide [®] Ultra	Notes
Length	105.1 in. (2,670 mm)	
Overall Width	54.7 in. (1,390 mm)	
Overall Height	56.3 in. (1,430 mm)	
Seat Height, Laden	27.1 in. (688 mm)	2
Seat Height, Laden (Low seat position)		
Seat Height, Laden (High seat position)		
Seat Height, Laden (Low seat position with optional ARH suspension)		
Seat Height, Laden (High seat position with optional ARH suspension)		
Seat Height, Unladen	28.9 in. (735 mm)	
Seat Height, Unladen (Low seat position)		
Seat Height, Unladen (High seat position)		
Seat Height, Unladen (Low seat position with optional ARH suspension)		
Seat Height, Unladen (High seat position with optional ARH suspension)		
Static Ground Clearance	4.9 in. (125 mm)	
Dynamic Ground Clearance (with optional suspension)		
Rake (steering head)	26	
Fork Angle	32.2	
Trail	3.96 in. (101 mm)	
Wheelbase	65.7 in. (1,670 mm)	
Tires, Type	Dunlop [®] Harley-Davidson Series, bias blackwall front and radial blackwall rear	
Tires, Front Model	D408F	
Tires, Front Specification	MT 130/60B19 M/C 61H	
Tires, Rear Model	TK100	
Tires, Rear Specification	P215/45R18 83T	
Fuel Capacity	6 gal. (22.7 l)	

Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5 qt. (4.7 l)	
Transmission Capacity	1.1 qt. (1 l)	
Primary Chain Case Capacity	1.1 qt. (1 l)	
Coolant Capacity	0.8 qt. (0.75 l)	
Weight, As Shipped	1,199 lb. (544 kg)	
Weight, In Running Order	1,237 lb. (561 kg)	
Gross Vehicle Weight Rating	1,700 lb. (771 kg)	
Gross Axle Weight Rating, Front	511 lb. (232 kg)	
Gross Axle Weight Rating, Rear	1,189 lb. (539 kg)	
Luggage Capacity -Volume	6.8 cu ft (0.19 m3)	

Engine	FLHTCUTG Tri Glide® Ultra	Notes
Engine	Twin-Cooled™ Milwaukee-Eight® 114	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore	4.016 in. (102 mm)	
Stroke	4.5 in. (114.3 mm)	
Displacement	114 cu in (1,868 cc)	
Compression Ratio	10.5:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	Paper, washable	
Exhaust	2-1-2 dual exhaust with tapered mufflers	
Lubrication System	Pressurized, dry-sump	

Drivetrain	FLHTCUTG Tri Glide® Ultra	Notes
Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 30/70 ratio	
Clutch	Mechanically actuated 10 plate, wet Assist & Slip	
Transmission	6-Speed Cruise Drive	
Gear Ratios (overall) 1st	10.534	
Gear Ratios (overall) 2nd	7.302	

Gear Ratios (overall) 3rd	5.423	
Gear Ratios (overall) 4th	4.392	
Gear Ratios (overall) 5th	3.741	
Gear Ratios (overall) 6th	3.157	

Chassis	FLHTCUTG Tri Glide® Ultra	Notes
Frame	Mild steel, square-section backbone with twin down-tubes	
Swingarm	Mild steel, rectangular tube sections with plate junctions; MIG welded	
Front Fork	49mm dual bending valve	
Front Fork, Optional		
Rear Shocks	Hand-adjustable emulsion rear suspension	
Rear Shocks, Optional		
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Black, 7-spoke Cast Aluminum	4
Wheels, Front Diameter	19 in. (483 mm)	
Wheels, Front Width	3.5 in. (89 mm)	
Wheels, Rear Type	Black, 7-spoke Cast Aluminum	4
Wheels, Rear Diameter	18 in. (457 mm)	
Wheels, Rear Width	5.5 in. (140 mm)	
Brakes, Caliper Type	Front: 32mm 4 piston fixed, Rear: floating 36mm piston integrated park brake	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5.1 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	10.6 in. (270 mm)	
Brakes, Rear Thickness	0.24 in. (6 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	3 in. (76 mm)	

Performance	FLHTCUTG Tri Glide® Ultra	Notes
--------------------	----------------------------------	--------------

Engine Torque Testing Method	J1349	
Engine Torque	120 ft-lb (163 Nm)	5
Engine Torque (rpm)	2,500	
Power	93 HP / 69 kW @ 5020 rpm	
Lean Angle Testing Method	N/A	
Lean Angle, Right (deg.)	N/A	
Lean Angle, Left (deg.)	N/A	

Electric	FLHTCUTG Tri Glide® Ultra	Notes
Battery	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca (per Battery Council International Rating)	
Charging	Three-phase, 48-amp system (600W @ 13V, 2000 rpm, 625W max power @ 13V)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	LED 34-watt, 915 lumen low beam, 37-watt, 915 lumen high beam with switchable 20-watt, 1,220 lumen LED Fog Lamps. Total of 2,136 lumen output at low beam with fog lights.	
Lights (as per country regulation), Tail/Stop	Incandescent	
Lights (as per country regulation), Front Signal Lights	Incandescent	
Lights, Rear Turn Signals	Incandescent	
Gauges	Speedometer, tachometer, fuel, and voltage gauges; display features odometer, trip A, trip B, range to empty, gear indicator	
Auxiliary Lamps	LED fog	
Electric Power Outlet	Electric power accessory port in fairing	
GPS System	Boom!™ Box GTS audio system with GPS and touchscreen	
Reverse Gear	Electric reverse actuated by handlebar mounted hand controls	

Fuel Economy & CO₂ Emissions	FLHTCUTG Tri Glide® Ultra	Notes
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	42 mpg (5.6 l/100 km)	

Infotainment	FLHTCUTG Tri Glide® Ultra	Notes
Infotainment system	Boom!™ Box GTS	
Screen Size	6.5 in (165 mm)	
Type	Full Color TFT	
Watts Per Channel	25	
Speakers	4	
Speaker Size	5.25 inch (133 mm)	
Headset Specifications (if equipped)	16 - 64 ohms	
AM	Standard	
FM	Standard	
MW	N/A	
LW	N/A	
Weather Band (WB)	Standard (USA & Canada only)	
SD Card, Flash Drive and MP3 - via USB Connection	Supported	
Hands-free Mobile Phone - via Bluetooth	Standard	
Voice Recognition Languages: Phone functions only	Phone dependent	
Rider/Passenger Intercom	Standard (Passenger Headset Sold Separately)	
Vehicle Information Screen (Air temperature, oil pressure and EITMS)	Standard	
Text-to-Speech (TTS) Languages	Phone dependent	
USB	USB/MTP/iPod/iPhone	
Phone Connectivity		
Bluetooth	Phone/Media Supported	
Navigation - via Bluetooth		

Rider Safety Enhancements	FLHTCUTG Tri Glide® Ultra	Notes
Anti-lock Brake System (ABS)	Included	
Electronic Linked Braking (ELB)	Included	
Traction Control System (TCS)	Included	
Drag-torque Slip Control System (DSCS)	Included	
Vehicle Hold Control (VHC)	N/A	
Tire Pressure Monitoring System (TPMS)	N/A	

Wheel Lift Mitigation	N/A	
-----------------------	-----	--

Cornering Rider Safety Enhancements	FLHTCUTG Tri Glide® Ultra	Notes
Cornering Enhanced Anti-lock Brake System (C-ABS)	Included	
Cornering Enhanced Electronic Linked Braking (C-ELB)	Included	
Cornering Enhanced Traction Control System (C-TCS)	Included	
Cornering Drag-Torque Slip Control System (C-DSCS)	N/A	
Enhanced Lift Mitigation	N/A	

Warranty And Service	FLHTCUTG Tri Glide® Ultra	Notes
Warranty	24 months (unlimited mileage)	6
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	7

Footnotes	FLHTCUTG Tri Glide® Ultra	
1	<p>Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed)</p>	

	and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.	
2	Measurement reflects 180 lb. (81.7 kg) operator weight.	
3	Recommended 91 octane or higher fuel (R+M)/2.	
4	Standard and optional wheels may vary by country and region.	
5	Values shown are nominal. Performance may vary by country and region.	
6	See motorcycle owner's manual for complete details.	
7	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.	

©2025 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.